# **SOLUTIONS TO** STATIC PROBLEMS PACKAGING


## **BLISTER PACKAGING APPLICATIONS**

The thermo-vacuum forming process is static generative with the result that the stack of tray can be highly charged. Sometimes there is a problem de-nesting the trays, which can be overcome with a Fraser Ionised Air Nozzle, but more usually the static problems are associated with filling of the trays with product. Typical static problems are:



### Static Shocks

The metal lid on the blister pack is a floating conductor - it can be induction charged by the static in the plastic part of the pack and that charge is available to give a shock. The charge in a single pack is quite small, but if it goes into a larger container the accumulated charge can give painful shocks. Some reduction in charge can be achieved by a 660 Static Discharger with its Stainless Steel filaments touching the lid as it comes out of the machine. Alternatively, neutralise the whole container with a 3850 Bar as illustrated.



#### **Dust on the Shoulder**

Product dust and powder on the shoulder of the tray prevent the lid from making a good seal. This dust can be removed by a flow of air from a 1250 Air Bar in conjunction with a simple dust collection system. The airflow must be regulated to avoid disturbing the product.



#### **Product Jumping Out**

If there is a high charge in the tray it can repel the product or at least some of the powder coating around the product. The tray can be neutralised with a 1250 Bar immediately before the filling station to prevent this.

