

| CRANE TECHNICAL INFO            |                             |
|---------------------------------|-----------------------------|
| Crane Model:                    | Liebherr MK110              |
| Total Crane Weight (travel):    | 64.00 ton                   |
| Max. Axle Weight (no. axles):   | 13.50 ton (5)               |
| Main Boom Extended:             | 52.00 m                     |
| Telescopic Sections:            | n/a                         |
| Fly Jib length / angle:         | n/a                         |
| Counterweights:                 | 3.80 ton                    |
| Outrigger Base Centres:         | 8.25 x 8.20 m               |
| Max. Outrigger Jack Point Load: | 35 ton                      |
| Standard Outrigger Mat Size:    | 1.00 x 1.00 m               |
| Additional Mats - Base Area:    | n/a                         |
| Effective Bearing Area of Mat:  | 1.00 sq m                   |
| Max. Pressure Through Mat:      | 35.00 t / m sq              |
| Max. Working Wind Speed:        | 14.00 m per sec (operating) |
| Capacity:                       | 2.10 ton @ 46.00 m radius   |

| LOAD DETAILS OF ITEM LIFTED |          |  |  |  |  |  |  |
|-----------------------------|----------|--|--|--|--|--|--|
| Item Weight:                | 2.00 ton |  |  |  |  |  |  |
| Lifting Tackle:             | 0.05 ton |  |  |  |  |  |  |
| Lifting Beam / Device:      | n/a      |  |  |  |  |  |  |
| Reduction For Fly:          | n/a      |  |  |  |  |  |  |
| Reduction For Guyed Mast:   | n/a      |  |  |  |  |  |  |
| Hook Block:                 | included |  |  |  |  |  |  |
| Total Load:                 | 2.05 ton |  |  |  |  |  |  |
| Capacity:                   | 2.10 ton |  |  |  |  |  |  |
| Useable Capacity:           | 0.05 ton |  |  |  |  |  |  |
| % Capacity Used:            | 97.62    |  |  |  |  |  |  |
|                             |          |  |  |  |  |  |  |

## Radius and capacity

| 8.25 m x 8.20 m           |      |                    | m/k  | кg   |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|---------------------------|------|--------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| max. 8 Bft<br>(20 m/sec.) | m    | m / kg             | 14.0 | 18.0 | 22.0 | 26.0 | 28.0 | 30.0 | 32.0 | 34.0 | 36.0 | 38.0 | 40.0 | 42.0 | 44.0 | 46.0 | 48.0 | 50.0 | 52.0 |
| <b>→ V</b>                | 52.0 | 3.4 – 14.7<br>8000 | 8000 | 6370 | 5060 | 4180 | 3830 | 3530 | 3280 | 3050 | 2850 | 2670 | 2500 | 2360 | 2230 | 2100 | 1990 | 1890 | 1800 |
|                           | 44.0 | 3.4 – 15.1<br>8000 | 8000 | 6550 | 5220 | 4300 | 3950 | 3640 | 3380 | 3140 | 2940 | 2750 | 2590 | 2440 | 2300 |      |      |      |      |







| Mobile: 07958 813047                  |
|---------------------------------------|
| Email: g.davies@craneconsultancy.co.u |
| Web: www.gdcraneconsultancy.co.uk     |

| Client Name:         | F  |                    |                  | Rev | Date | Detail           | Chkd | Appr | г |
|----------------------|--|--------------------|------------------|-----|------|------------------|------|------|---|
| Site Address:        | Coventry   |                    |                  |     |      | Plan & Elevation |      | -    |   |
| Title / Description: | Lifting glass stillages & materials to building roof |                    |                  |     |      |                  |      |      | 1 |
| Scale of Dwg:        | 1:500 @ A4   |                    |                  |     |      |                  |      |      | Ì |
| Dwg Status:          | Approved for Lifting                                 |                    |                  |     |      |                  |      |      | ١ |
| I.D Number:          | Drawn By:  | Date Drawn:        | Revision Number: |     |      |                  |      |      | t |
| GD/XTR/0004          | Gary Davies 40.                                      | 26th February 2018 | 0                |     |      |                  |      |      |   |

Do not scale drawing
Client to provide safe access to rigging area
Client to provide crane base hardstanding
No crane movements to be unaccompanied
No persons not involved with lift allowed into
the segregated area

